

LC Series

LC1.538P

LED Display Light Everywhere



Product features:

- 320X160mm universal size
- Bottom case texture design
- High-quality lamp beads

Lamp beads do not fall off easily.




- New design of PCB board is more reliable
- Lightweight installation

Module as a unit for assembling, reduced screen weight, reduce the structural load of the building.

- Excellent visual experience
- Good Compatibility

Replace the indoor *P1.2~P4* module with the same series.

- Support for coating process*
- Supports 45° tangent angle*
- Standard refresh rate up to 4200Hz*



Note: Drawings are for reference only.

SPECIFICATION PARAMETERS:

	Parameter	Value
Module	Pixel Pitch	1.538mm
	LED Type	SMD1212
	Module Resolution (W×H)	208*104=21632 Pixels
	Pixel density (pixels/sq.m.)	422500 dot/m ²
	Module Size (WxHxD)	W320mmxH160mmxD16.6mm
	Module Weight	0.49±0.02kg
	HUB	HUB75
	Module power supply voltage	4.2V
Optical	Single-dot Brightness Calibration	Support
	Brightness	≥600 cd/m ²
	Color Temperature	3000 ÷ 9500 K Adjustable
	Beam Angle (Hor/Ver°)	160°/140°
	Brightness/Color Uniformity	≥98%
	Contrast Ratio	5000:1
Electroni	Input Power <Max>	448 W/m ²
	Input Power <Typical>	163 W/m ²
	Power Supply Input Voltage	AC90 ~ 132V/ AC186 ~ 264V, Frequency 47-63 (Hz)
Performance	Frame Changing Frequency	60Hz
	Drive mode	Constant Current Driving
	Scanning method	52S
	Refresh Rate	≥4200Hz
	Processing Depth	12~14Bit
	Video Support	2K HD, 4K UHD
Environm	Life Span (hrs)	100000hrs
	Working Temp/Humidity (°C/RH)	-20°C~45°C / 10%~80%RH (No Condensation)
	Storage Temp/Humidity (°C/RH)	-20°C~50°C / 10%~65%RH (No Condensation)
	Certification	BIS/CE/CB/ROHS/EAC

Note:

- 1.Product pictures are for illustration only, the actual product effects (including but not limited to appearance, color, size) may be slightly different, please refer to the actual product.
- 2.The specification parameters are reference values. Part of the data comes from Unilumin' s internal laboratory and is obtained under a specific test environment. In actual use, it may be slightly different due to product batch differences, configuration differences, software versions, use conditions and environmental factors. Actual usage shall prevail.
3. Different configurations can achieve different refresh rates.
4. To enhance the user experience, please use the recommended control system brand and model.