

Instantaneous Water Boiler



WM-12



WM-30



WM-35-1



WM-60-1 / WM-80-1



WM-60F-1 / WM-80F-1



WM-100-1 / WM-180-1 / WM-200-1

	Code	Dimension (mm)	Voltage	Electric (kW)	Water Output (L/Hr)
Counter Top	WM-12	212 x 312 x 430	220V/SPN	1	15
	WM-30	300 x 282 x 470	220V/SPN	1.5	20
	WM-35-1	220 x 438 x 490	220V/SPN	2	30
	WM-60-1	345 x 355 x 675	220V/SPN	2.85	55
	WM-80-1	345 x 355 x 675	380V/TPN	6	90
Slim Version	WM-60F-1	220 x 480 x 675	220V/SPN	2.85	45
	WM-80F-1	220 x 480 x 675	380V/TPN	6	80
Bulk Volume Version	WM-100-1	510 x 440 x 950	380V/TPN	9	180
	WM-180-1	510 x 440 x 950	380V/TPN	15	200
	WM-200-1	510 x 440 x 950	380V/TPN	18	240

	IN ↓	OUT ↓	Certification
All Models	DN15	DN15	CE

Tower Tap Dispenser



WM-32UHC



WM-32UHCS-A



WM-35UH



WM-35UHC



WM-35UHW

	Code	Tank Dimension (mm)	Voltage	Electric (kW)	Water Output (L/Hr)	92-97°C	10°C	Ambient	Sparkling
Hot	WM-35UH ¹	320 x 235 x 490	220V/SPN	2	27	-	-	-	-
Hot & Cold (Hotel Room Ver.)	WM-32UHC ¹	320 x 465 x 340	220V/SPN	1.0+0.4 = 1.4	15	20.5	-	-	-
Hot & Cold	WM-35UHC ¹	500 x 535 x 400	220V/SPN	2.2+0.5 = 2.7	29	20	-	-	-
Hot & Ambient	WM-35UHW ¹	320 x 345 x 490	220V/SPN	2	27	-	156	-	-
Hot & Cold & Sparkling	WM-32UHCS-A ¹	488 x 500 x 420	220V/SPN	1.0+0.2 = 1.2	18	22.5	-	18	-

¹ Color options for tower faucet: Rose Gold / Black / Chrome finishing. Optional height extension kit (Ø55 x 107mm H) for tower faucet (Standard Spout height at 160mm H). Specify when ordering.

	IN ↓	OUT ↓	Certification
All Models	DN15	DN15	

**Instantaneous Water Boiler
I-Aqua Classic**



C L A S S I C
R E W I N D

Key To High Quality Water Preparation

With guarantee water output temperature at 92°C+, we ensure water is safe to drink at all time.



IWB-35

IWB-60 /
IWB-80

IWB-60F /
IWB-80F

IWB-100

	Code	Dimension (mm)	Voltage	Electric (kW)	Water Output (L/Hr)
Counter Top	IWB-35	212 x 366 x 471	220V/SPN	2	30
	IWB-60	340 x 350 x 650	220V/SPN	2.85	55
	IWB-80	340 x 350 x 650	380V/TPN	6	90
Slim Version	IWB-60F	220 x 485 x 650	220V/SPN	2.85	45
	IWB-80F	220 x 485 x 650	380V/TPN	6	80
Bulk Volume Version	IWB-100	510 x 435 x 930	380V/TPN	9	180

All Models



DN15



DN15

Tea Brewing Machine & Coffee Urn



T E A
B R E W I N G
E X P E R T

Automation of Tea Brewing System

To maintain the consistency and intensify of the tea quality, our machine equips with built-in water circulation system to elevate the tea brewing procedure.



TC-040



TC-5



TC-010



With a precise control interface, operator can complete the complicated tea brewing process in a simple press

	Code	Tank Dimension (mm)	Voltage	Electric (kW)	Rated Capacity (L)	Tank Capacity (L)
Tea Brewing Machine	TC-010-A	270 x 500 x 800	220V/SPN	2.4	9	5 x 1nos
Tea Brewing Holder	TC-5 ¹	270 x 360 x 386+100	220V/SPN	0.4	-	5 x 1nos
Coffee Urn	TC-040	630 x 518 x 730	380V/TPN	9	26	10.5 x 2nos

¹ It is a removable tank for holding brewed tea for serving. An optional accessories for TC-010-A.



All Models

DN15

DN15