



# HT330

## 4" Rugged Handheld Terminal

Android 12 with GMS certified | Removable 5200mAh battery | IP67 rating & 1.5M drop



Transform your task with Unitech's HT330 — rugged handheld terminal embedded with an unrivaled 2D engine and running on the latest Android 12. The latest Android 12 platform with GMS provides an intuitive interface to manage data effectively on a 4-inch screen and has integrated all features you need from stock checking to shipping. As a reliable work companion, HT330 shows outstanding software support as well as trustworthy scanning hardware that optimizes work performance. The removable 5200mAh Lithium-ion battery carries your task for over 20 hours, allowing a full shift to go on. Reaching IP67 enterprise protection and withstanding 1.5 drop makes HT330 a perfect tool to maximize data collection, management, and traceability in nearly every practice of retail, transportation & logistics, manufacturing, and more!

### Choice of Optimum Scanning

When it comes to facilitating work efficiency and minimizing errors at service, HT330 is the best choice of optimal data collection terminal for the retail and warehousing field. This high-performance handheld terminal featuring a powerful 2D engine has upgraded to Android 12 OS to empower staff with an easy-scan, simple-check convenience. The GMS certification allows staff to access a set of pre-installed apps and services meant to boost productivity.

### Extending Battery Capacity for All Day

A larger battery capacity of HT330 means fewer battery replacements and longer operation time. The removable 5200mAh Lithium-ion battery supports 20 working hours, making it a suitable device for intensive scanning scenarios, like inventory checks. The 3GB RAM/32GB Flash memory storage undertake a high volume of data even after hours.

### Rich and Reliable Wireless Connection

The 802.11 a/b/g/n/ac/d/e/h/i/j/k/r/v standards and faster transmission synchronize information in real-time to ensure barrier-free communication. HT330 lays a foundation of instant visibility into what's happening and being done under 2.4G+5GHz bandwidth. The Bluetooth® 5.0 improves the connectivity of related pairing devices, and the GPS function further tracks location more precisely.

### Friendly Panel in Rugged housing

The one-hand terminal combines a 4-inch touchscreen with 32 keys physical keypad, providing a flexible interface to satisfy industries' requirements. Water-resistant, dust-proof, and enduring drop to 1.5 m, HT330 can handle all demanding environments.

### Features

- Powerful 2D Engine supporting major 1D/2D barcodes
- Android 12 OS with GMS-certified
- Full-shift 20 hours operation time
- Removable 5200mAh Lithium-ion battery
- Friendly panel design: 4" Touchscreen / Intuitive Backlight 32 Keys Keypad
- Ergonomic and balanced weight 295g
- Clear camera recognition: Rear 13MP, Front 5MP
- Support wireless Bluetooth® 5.0
- Enterprise Ruggness: IP67 rated protection/ 1.5M drop-to-concrete
- Support 802.11 a/b/g/n/ac/d/e/h/i/j/k/r/v standards under 2.4G+5GHz frequency
- Support MDM software and utilities such as MoboLink, StageGO, SOTI, Ivanti Wavelink, etc.



### System Features

OS	Android 12
GMS certified	YES
CPU	Octa-core 2GHz
Memory	3GB RAM / 32GB Flash
Languages support	Multi-languages

### Display

4", WVGA 800 X 480, Backlight (450nits)  
Multi-touch panel, gloves and wet hands supported

### Buttons / Keypad

Numeric (32 keys); number keys, function and direction keys with backlight

### Camera

Rear 13 MP with PDAF, LED flash light  
5MP Front Camera

### Indicator

LED, Speaker, Vibrator

### Symbologies

1D Barcodes	Support all major 1D barcodes
2D Barcodes	Support all major 2D barcodes

### RFID

UHF	Optional
HF	Optional: Frequency 13.56Mhz, ISO14443A/B, ISO15693 standard, NFC, MIFARE, Felica

### Power Source

Main battery 3.85V 5200mAh Li-ION battery (removable),  
Operating time : over 20 hours  
(depending on the specific environment)

### Regulatory Approvals

CE, FCC, NCC, CCC, SRRC, VCCI, TELEC, RoHS, BQB, N-Mark, BSMI

### Communication

Bluetooth®	Bluetooth® 5 supported
WLAN	802.11 a/b/g/n/ac/d/e/h/i/j/k/r/v, fast roaming, 2.4G+5GHz, hotspot
WWAN	4G: FDD-LTE B1/2/3/4/5/7/8/12/17/20/28a&b/66 TDD-LTE B38/39/40/41 3G: WCDMA B1/2/4/5/8 2G: GSM B2/3/5/8
GPS	GPS/AGPS, GLONASS, BeiDou, Galileo
Sensors	Gyroscope, G-sensor, E-Compass, Light & Proximity Sensor

### I/O Interfaces

USB	USB 2.0 (Type-C)
OTG	Yes, over USB Type-C
POGO PIN	Pogo Pin Rear: Support Gun grip Pogo Pin Bottom: Charging via cradle Pogo Pin Rear: Support UHF Gun Grip (optional)
SIM Slot	Nano SIM Slot x 2
Expansion Slot	MicroSD memory card up to 256GB
Audio	Speaker: 1W output, 90 dB at 10cm MIC: 2 MIC design

### Enclosure

Dimensions ( H x W x D )	185 mm x 70 mm x 23.8 mm
Weight	295g with battery

### Environmental

Operating temperature	-20°C to 60°C
Storage temperature	-40°C to 70°C (without battery)
Charging temperature	0°C to 45°C
Relative Humidity	5% ~ 95% (non-condensing)
Drop Specification	1.5m / 1.8m (with boot case)
Sealing	IP67

### Software

MDM Software	SOTI, Ivanti Wavelink, 42Gears, and MoboLink
--------------	--

### Accessories

3.85V 5200mAh battery	Glass Screen Protector
USB Type C Cable	Gun Grip
Hand Strap	Single Slot Charging Cradle
Stylus with coil strap	Single Slot USB Cradle
Boot Case	



### Headquarters

Taipei, Taiwan  
http://www.ute.com e-mail: info@hq.ute.com

### unitech America

Los Angeles  
http://us.ute.com e-mail: info@us.ute.com  
http://can.ute.com info@can.ute.com  
Mexico  
http://latin.ute.com e-mail: info@latin.ute.com

### unitech Asia Pacific & Middle East

Taipei  
http://apac.ute.com info@apac.ute.com / info@india.ute.com  
http://mideast.ute.com info@mideast.ute.com

### unitech Europe

Tilburg / Netherlands  
http://eu.ute.com e-mail: info@eu.ute.com

### unitech Japan

Tokyo  
http://jp.ute.com e-mail: info@jp.ute.com

### unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen  
http://cn.ute.com info@cn.ute.com  
Taipei http://tw.ute.com info@tw.ute.com

