



Smart IR

AI Motorized V.F. Bullet IR Network Camera



Fine quality made in Taiwan

Features


- ★ 5MP SONY Starvis back-illuminated CMOS sensor, NDAA compliant.
- ★ Smart IR, combines high and low beams to adjust intensity for different lighting conditions.
- ★ Support H.264 / H.264+ / H.265 (HEVC) / H.265+ / MJPEG compression format.
- ★ Built-in motorized auto focus 2.7~13.5mm 5X zoom lens (Optional 7~22 mm).
- ★ Support 120dB HDR, 3DNR, BLC, AWB and Defog technology to restore clear images in foggy days.
- ★ Support 30fps high frame rate, easy to capture images without lag in high-speed motion.
- ★ Support Micro SD/SDHC/SDXC card storage up to 1TB.
- ★ Support API / ONVIF (G/Q/S/T) protocol.
- ★ AI Deep Learning, built-in multiple intelligent analysis functions.
- ★ Support RJ45 10/100M, built-in POE 802.3af network power supply.
- ★ Support mobile monitoring (iPhone / iPad / Android / Android Pad).
- ★ Support various browsers (IE8~11 / Chrome / Firefox / Safari) and client software (VMS).
- ★ SIP (Session Initiation Protocol) provides audio/alarm/intercom & video streaming for mobile & video telephony.
- ★ IK10 vandal-proof & IP67 weatherproof housing.
- ★ Enable Smart Stream to save bandwidth, storage space and bit rate (ex: H.265+ saves 70%~80% bandwidth compared to H.264)
- ★ Support NAS (NFS/SMB/CIFS) network storage / ANR.

Specifications

Model No.	NS5B4R
CMOS Image Sensor	1/2.8" 5MP SONY Starvis Back Illuminated CMOS Sensor
Effective Pixels (HxV)	2592x1944
Compression Format	H.264 / H.264+ / H.265 (HEVC) / H.265+ / MJPEG
Video Format Standard	NTSC / PAL
Elec. Shutter Speed	1/100,000s
Minimum Illumination	0.005 LUX @F1.4 / 0 LUX @ IR
S/N Ratio	≥ 55 dB
Wide Dynamic Range	120dB
System Scan	Progressive
Video Output	Network
Lens Furnished	5MP HD Motorized Vari-Focal Auto Focus 2.7~13.5mm 5X zoom lens (Optional 7~22mm)
Focus Control	Manual / Auto
Angle of View	2.7~13.5mm: H99~31°/D124~38°/V72~23° / 7~22mm: H37~15°/D46~19°/V28~11°
Day & Night	Day / Night / Auto / Custom / Schedule
IR Projection Distance	> 50M
Main Stream	60Hz: 30fps@2592x1944 / 2592x1520; 45fps@2048x1536; 60fps@1920x1080 / 1280x960 / 1280x720 50Hz: 25fps@2592x1944 / 2592x1520; 45fps@2048x1536; 50fps@1920x1080 / 1280x960 / 1280x720
Sub Stream	60Hz: 60fps@704x576 / 640x480 / 640x360 / 352x288 / 320x240 50Hz: 50fps@704x576 / 640x480 / 640x360 / 352x288 / 320x240
3rd Stream	60Hz: 30fps@1920x1080 / 1280x720 / 704x576 / 640x480 / 640x360 / 320x240 50Hz: 25fps@1920x1080 / 1280x720 / 704x576 / 640x480 / 640x360 / 320x240
Video Bit Rate	16Kbps~16Mbps (CBR/VBR adjustable)
Image Mask	Up to 8 areas
ROI (Region of Interest)	Up to 8 zones
Image Configuration	Brightness / Contrast / Saturation / Sharpness
Ethernet	1*RJ-45 10/100M

Network Storage	NAS (Supports NFS, SMB / CIFS) / Internet-disconnected Smart Recording (ANR)
Network Protocol	IPv4/IPv6 / ARP / TCP / UDP / RTCP / RTP / RTSP / RTMP / HTTPS / DNS / DDNS / DHCP / FTP / NTP / SMTP / SNMP / UpnP / Bonjour / SIP / PPPoE / VLAN / 802.1x / QoS / IGMP / ICMP / SSL / TLS 1.2
Intelligent Analysis	Region Entrance / Region Exiting / Advanced Motion Detection / Tamper Detection / Line Crossing / Loitering / Object Left / Object Removed
Advanced Functions	Heat Map / BLC / HLC / 2D DNR / 3D DNR / Defog / AWB / IP Address Filtering / AGC / Anti-Flicker / Corridor Mode / Deblur / Watermark
Face Detection	Detect and capture faces, get real-time snapshots
People Counting & Report	Count the number of people entering or exiting, up to 4 detection areas for regional people counting
SIP/VoIP	Support
Audio	Multi-Interface Version: 1CH input / 1CH output; Bit Rate: 16~256kbps; Compression: G711/AAC/G722/G726; Sample Rate: 8/16/32/44.1/48KHz
Two-way Audio	Support
Alarm	Multi-Interface Version: 1CH input / 1CH output
Memory Card Slot	Support Micro SD / SDHC / SDXC Card Local Storage (Up to 1TB)
Event Trigger	Motion Detection / Network Disconnection, etc.
Event Action	FTP Upload / SMTP Upload / SD Card Record / SIP Phone / HTTP Notification, etc.
Housing Material	Metal IK10 Vandal-proof & IP67 Weatherproof
Operating Environment	Temperature: -40°C to 60°C (-40°F to 140°F) / Humidity: 0~95% Non-condensing
Protocol	API / ONVIF Profile (G/Q/S/T)
Power Supply	DC12V±10%, Built-in POE, Support 802.3af
Power Consumption	Max. 6W / 9W (IR On)
P2P	Support
Dimensions (mm)	76(D) x 239.5(L)mm
Weight (g)	825g


Dimensions



Optional Junction Box

- ★ **Model No.:** XPBS4J
- ★ **Weight:** 620g
- ★ **Dimension:** 134 x 126 x 40 mm
- ★ **Installation Environment:** For the containing of electrical connections which need to be concealed from sight and deter tampering

Infrastructure



Slight specification variations may occur due to product enhancement to optimize functionality