



9CH

16CH

32CH


NDA  
Compliant



4K / 12MP

## Real Time Multiplex Smart Network Video Recorders

XCore  
Technology



*Fine quality made in Taiwan*

# Features


- ★ 9CH & 16CH NVR with 1\*SATA: Support 4K network camera video and audio access.
- ★ 16CH NVR with 2\*SATA & 32CH NVR with 4\*SATA: Support 12MP network camera video and audio access.
- ★ Equipped with Novatek CPU (made in Taiwan) for a higher level of information security.
- ★ Support H.264 / H.264+ / H.265 / H.265+ compression algorithm technology.
- ★ Support HDMI & VGA video output.
- ★ Support up to 4K (3840x2160) HDMI resolution.
- ★ Support cloud service, plug and play, no need static IP.
- ★ Active event notification via App, push status & video.
- ★ Support digital zoom.
- ★ Built-in standard ONVIF protocol.
- ★ Support Pelco-D / Pelco-P protocol.
- ★ Support mobile monitoring (iPhone / iPad / Android / Android Pad).
- ★ Support various browsers (IE8~11 / Chrome / Firefox / Safari) and client software (VMS) for Mac & Windows.

# Specifications

	9CH	16CH	16CH	32CH
<b>Model No.</b>	XNR265-4K09W	XNR265-4K16W	XNR265-1216WS2	XNR265-1232WS4
<b>CPU</b>	Novatek SoC (NDAA Compliant)			
<b>Operating System</b>	Embedded Linux			
<b>Digital Video Input</b>	9CH up to 4K (3840x2160)	16CH up to 4K (3840x2160)	16CH up to 12MP (4000x3000)	32CH up to 12MP (4000x3000)
<b>Compression Format</b>	H.264 / H.264+ / H.265 / H.265+			
<b>Video Output Resolution</b>	<b>HDMI</b>	3840x2160(4K)@30Hz / 1920x1080@60Hz / 1280x1024@60Hz / 1280x720@60Hz / 1024x768@60Hz		
	<b>VGA</b>	1920x1080P@60Hz / 1280x1024@60Hz / 1280x720@60Hz / 1024x768@60Hz		
<b>Split Screen</b>	1 / 4 / 9	1 / 4 / 9 / 16	1 / 4 / 6 / 8 / 9 / 10 / 13 / 16	1/4/6/8/9/10/13/16/17/25/36
<b>Resolution</b>	4K / 5MP / 4MP / 3MP / 1080P / 960P / 720P / D1		12MP / 4K / 5MP / 4MP / 3MP / 1080P / 960P / 720P / D1	
<b>Audio Input</b>	1CH RCA		1CH RCA Support 16CH IPC Audio Input	1CH RCA Support 32CH IPC Audio Input
<b>Audio Output</b>	1*RCA (Linear, 1kΩ) / Bit Rate: 64kbps / Compression: G711u / G711a / ADPCM_DVI4			
<b>Voice Intercom</b>	Support one-way		Support two-way	
<b>Alarm</b>	NIL	Input: 4CH / Output: 4CH	Input: 4CH / Output: 1CH	Input: 16CH / Output: 4CH
<b>Motion Detection</b>	9CH 396 area (22x18)	16CH 396 area (22x18)		32CH 396 area (22x18)
<b>Trigger Event Log</b>	Email / FTP / Snapshot / Screen Tips / Buzzer		Sound Recording / Email / FTP / Snapshot / Screen Tips / Buzzer / Alarm Output	
<b>Digital Zoom</b>	Support			
<b>OSD Display</b>	Camera Title / Time / Recording / Motion Detection / Event Alarm			
<b>Recording Rate</b>	4K@8CH * 25/30fps 5MP / 4MP / 3MP / 1080P / 960P / 720P / D1 @9CH * 25/30fps	4K@10CH * 25/30fps 5MP / 4MP / 3MP / 1080P / 960P / 720P / D1 @16CH * 25/30fps	12MP / 4K / 5MP / 4MP / 3MP / 1080P / 960P / 720P / D1 @16CH * 25/30fps	12MP / 4K / 5MP / 4MP / 3MP / 1080P / 960P / 720P / D1 @32CH * 25/30fps
<b>Recording Mode</b>	Manual / Timer / Motion Detection / Smart Alarm			
<b>Decoding Capability</b>	4CH 1080P@30fps		1080P@240fps	1080p@480fps


	<b>9CH</b>	<b>16CH</b>	<b>16CH</b>	<b>32CH</b>
<b>Model No.</b>	XNR265-4K09W	XNR265-4K16W	XNR265-1216WS2	XNR265-1232WS4
<b>Local Playback</b>	1CH: 4K/5MP 2CH: 4MP/3MP 4CH: 1080/960/720P	4CH: 4KP 6CH: 5MP 8CH: 4MP 16CH: 1080P/960P/720P/D1	3CH: 12MP 4CH: 4K 8CH: 4MP 16CH: 1080P/960P/720P/D1	
<b>Remote Sync. Playback</b>	Support			
<b>Search Mode</b>	All / Channel / Manual / Time / Date / Motion Detection / Event Alert / Tag Search			
<b>Playback Mode</b>	Play / Pause / Stop / Fast Play / Slow Play / Rewind / Frame Play / Frame Rewind / Digital Zoom / Full Screen			
<b>Backup Method</b>	USB device (FAT32) / Network			
<b>Network Port</b>	1*RJ-45 10/100M Ethernet	1*RJ-45 10/100/1000M Ethernet		
	Built-in 6KV Anti-Static Protection			
<b>Incoming Bandwidth</b>	80M	100M	160M	320M
<b>Network Protocol</b>	TCP/IP / HTTP / UPnP / DNS / NTP / SMTP / DHCP / FTP / DDNS / RTSP / RTCP / P2P / PPPoE		TCP/IP / HTTP / UPnP / DNS / NTP / SMTP / DHCP / FTP / DDNS / RTSP / RTCP / P2P / PPPoE / IPv6 / HTTPS	
<b>P2P</b>	Support			
<b>ONVIF Version</b>	ONVIF 2.8		ONVIF S/T	
<b>Browser</b>	IE8~11 / Chrome / Firefox / Safari		IE8~11 / Chrome / Firefox / Safari / Edge	
<b>VMS (PC Client)</b>	Support Windows 7 / 8 / 10 11 & MAC OS			
<b>Mobile Devices</b>	iPhone / iPad / Android / Android Pad			
<b>Hard Drive Port</b>	1*SATA 2.5" / 3.5" (Each 8TB Max.)	2*SATA 2.5" / 3.5" (Each 10TB Max.)	4*SATA 3.5" (Each 10TB Max.)	
<b>USB Port</b>	2*USB2.0			1*USB2.0 / 1*USB3.0
<b>RS485</b>	1*RS485		NIL	1*RS485
<b>Power Supply / Consumption</b>	DC12V 2A / ≤6W (w/o HDD)		DC12V 4A / ≤15W (w/o HDD)	AC100~240V / ≤20W (w/o HDD)
<b>Operating Environment</b>	Temperature: -10°C to 50°C (14°F to 122°F) / Humidity: 10%~90% Non-condensing			

# Dimensions



**Model: XNR265-4K09W**  
**Model: XNR265-4K16W**


- Dimensions (mm):  
260(W) x 215(D) x 43(H)
- Net Weight:  
2.0KG (w/o HDD)



**Model: XNR265-1216WS2**

- Dimensions (mm):  
316(W) x 380(D) x 51(H)
- Net Weight:  
2.7KG (w/o HDD)


# Dimensions



**Model: XNR265-1232WS4**

- Dimensions (mm):  
440.8(W) x 372.1(D) x 71.9(H)
- Net Weight:  
3.5KG (w/o HDD)

# Infrastructure



Slight specification variations may occur due to product enhancement to optimize functionality